

Safety World

Camera Model LBG60SFP



LBG60SFP	
CCD/CMOS	CMOS
Image Sensor	IMX238
DSP	FH8520
Horizontal Resolution	1000TV Lines
Effective Pixels	1305(H)X1049(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/50-1/100, 000Sec; NTSC 1/60-1/100, 000Sec
Sync System	Internal
Usable Illumination	0.01Lux/F2.0
S/N Ratio	≥50dB
Gamma Correction	0.45
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec
Video Output	Composite Signal (1.0Vp-p, 75Ω)
Lens	
Focus Length	CS 6mm (4/8mm is optional)
Focus Control	Fixed
Lens Type	Fixed
Pixels	2M Pixels
Auto Iris Support	NO
Night Vision	
Infrared LED	Φ 42X2PC

Infrared Distance	40M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Camera Features	
Day/Night	Color/ B&W
OSD Menu Language	CN, EN, RU, IT
Defog	NO
Sense-up	NO
Smart-IR	NO
Wide Dynamic Range	DWDR
Backlight Compensation	YES
White Balance	AUTO
Gain Control	AUTO
Noise Reduction	3D NR
Privacy Masking	YES
Digital Zoom	YES
Picture Adjustment	YES
UTC Support	YES
General	
Weatherproof Housing	YES, IP66
Anti-cut Bracket	YES, 3-Axis
Dual Voltage	YES
IR Cut Filter	YES
Heater	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 700mA
Dimension	291.5(W)x101.5(H) x97.5(D)mm
Weight	1.7Kg

LEBANON – SAIDA – KAYA’A

WWW.SAFETYWORLD-LB.COM

INFO@SAFETYWORLD-LB.COM

+96103306082