

OVER Safe



CE FC RoHS

Specification:

| Model Number | SE-NR8204Q | SE-NR8209Q | SE-NR8216Q | |
|----------------------------|---|---|--|---|
| Operating System | Embedded LINUX operating system | | | |
| Image Code Control | Image code quality adjustable, variable bitstream and constant bitstream optional | | | |
| Dual Stream | Each channel can set main stream and sub stream | | | |
| Video Standard | 1080P(1920×1080)30fps/960P/(1280×960)/720P(1280×720)30fps | | | |
| Monitoring Image Quality | 1080P(1920×1080) / 960P/(1280×960)/720P(1280×720) | | | |
| Image Motion Detection | Each screen can set multiple detection areas and set 6-level sensitivity | | | |
| Recording Playback Quality | Any 4ch 1080P/720P playback simultaneously | | | |
| Region Cover | Every channel can set 4 cover regions | | | |
| Recording Mode | Support manual , auto, dynamic detection, alarm trigger record mode | | | |
| Backup Way | Support U disk, USB mobile HDD, USB DVD-RW . network storage and backup | | | |
| Operation Way | Mouse, remote control, front panel, keyboard controller | | | |
| Local Login | User name and password | | | |
| Recording Storage | Local HDD, network | | | |
| External Ports | Video Input | ① 2×(1920*1080) +2×(1280*720) IP camera ② 4×(1280*960) IP camera | ①9×(1920*1080) IP camera ② 4×(2048*1536) 3 mega IP camera | ①16×(1280*960)/(1280*720)IP camera ② 16×(1920*1080) IP camera ③4×(2048*1536) 3 mega IP camera |
| | Audio Input | 4ch network audio input | 9 ch network audio input | 16 ch network audio input |
| | Video Output | 1ch VGA+1ch HDMI | | |
| | Audio Output | 1ch BNC auxiliary output | | |
| | Network Port | 1 RJ45,10M/100M/1000M self-adaptive LAN port | | |
| | RS485 Port | Full duplex standard 485 port, support 19 kinds of PTZ protocols | | |
| | USB Port | 2 USB 2.0 ports | | |
| | Alarm Input | 4ch | 4ch | 4ch |
| | Alarm Output | 1ch | 1ch | 2ch |
| | Wireless Port | 3G, WIFI | | |
| HDD | HDD Port | 2 SATA HDD port | | |
| | MAX Capacity | Each port supports MAX 4TB HDD | | |
| Mobile Surveillance | Support(iPhone, Windows Mobile, BlackBerry, Symbian, Android) smart phone | | | |
| Power Supply | 12V4A | | | |
| Power Consumption | ≤25 (without HDD) | | | |
| Working Temperature | -10℃~+55℃ | | | |
| Working Humidity | 10%-90% | | | |
| Dimension | Equipment: 350mm×240mm×70mm, Packing: 409mm×365mm×129mm | | | |
| Weight(without HDD) | N.W.: 1.7Kg; with packing:2.89Kg | | | |
| Outside Carton | 5pcs/carton. 675mm×425mm×385mm; weight: 15.22 Kg. | | | |
| Installation Way | Desktop installation | | | |

Design and specification are subjected to be changed without prior notice.